



WWW.GTRADIAL.COM

© 2015 Giti Tire Pte. Ltd. All Rights Reserved

GTPCR201508ROW



PASSENGER CAR AND LIGHT TRUCK PATTERN DIGEST 2017

Why Buy Giti Tires?

Giti brand tires focus primarily on quality; providing comfortable, durable, and adaptable tires for drivers of all backgrounds.



A Focus on Production and Quality Management

In each of Giti's eight plants, the company sets the highest standard of quality procedures. A highly stringent quality control system and concern for the safety and quality demands in regions across the globe separates the brand from the competition.



Top Class R&D Facilities & Personnel

A team of over 600 experienced R&D engineers in five cutting-edge facilities around the world and top quality equipment ensure the upmost quality of tire production and delivery.



Awards and Recognition From the Best

The company has earned extensive recognition from highly credited organizations around the world and some of the automotive industry's largest names, including multiple top supplier awards from General Motors Brazil.



Respect Around the World

Giti Tire products are trusted by all types of individuals, from the everyday driver to top motorsports performers. Through top performance and an extensive dealer network, the brand has a reputation for quality, performance, and safety.



A Greater Mission

Giti Tire has an environmental and humanitarian drive that ties into all actions. The company focuses on multiple areas to properly educate people about driving and tire care, reduce energy consumption and pollution, as well as provide financial resources to help make the world a better place.

A Singapore Based Global Tire Company

Giti Tire has been in the tire business for more than 60 years.
The company has become one of the world's largest tire manufacturers,
serving customers in more than 130 countries.



2014 Revenue

USD 3.4 Billion



5 R&D and Testing Centers

4 R&D in Germany, USA, China, Indonesia,
and 1 testing center in UK



8 Manufacturing Plants

7 in China, 1 in Indonesia
1 in the US (scheduled to be operational in 2017)



10 Offices

Singapore, Indonesia, Malaysia, China, U.S.,
Canada, U.K., Germany, France, and Brazil



More than

33,000 Employees

Worldwide




More than

65,000 Points of Sale

In more than 130 countries



Giti Tire Worldwide Group Information



Giti Tire (China)



PT Gajah Tunggal Tbk (Indonesia)



Giti Tire (USA)



Giti Tire (Germany)



Giti Tire (United Kingdom)



Giti Tire (Brazil)

Cutting-Edge R & D Capabilities

Giti Tire has added two new R&D centers in the United States and Germany to the existing three centers in China, Indonesia, and the United Kingdom to further improve R&D capabilities around the world. With a team of over 600 experienced R&D engineers from 20 different nationalities working closely throughout the centers, Giti Tire continues to enhance brand competitiveness and brand position to become a market leader.

In addition to conducting research and development, Giti Tire also collaborates with leading research institutes and universities around the globe.



World Class Manufacturing Facilities

When you put on a set of Giti Tire on your vehicle, you can be confident that your tires have been put through one of the most rigorous and comprehensive quality control systems in the industry.

- Current construction of a full new tire production facility in South Carolina of the United States
- Eight Giti facilities have an annual capacity of well over 50,000,000 tires
- All plants have obtained ISO/TS16949:2002 accreditation (a highest standard of quality control) and ISO14001 Environmental Management System Accreditation
- Very strict quality controls and inspections at each stage of the production process to ensure that each component meets relevant specifications and standards



One of Giti's eight manufacturing bases



A Giti Tire production line



Internationally Accepted Product Quality and Accreditation




Passenger Vehicle Tire OEM:

Giti Tire has continued to strengthen its ambitions and relationships integral to developing its original equipment manufacturer (OEM) business. In conjunction with the company's strong developments in core areas such as technology, marketing, and quality management, Giti Tire has been awarded many contracts by existing and new OEM partners. This not only provides a steady demand from automotive producers themselves, but also increases demand and brand recognition in replacement markets.

In order to work more closely with our strategic partners, Giti Tire has employed dedicated OEM specialists in key markets such as India, Brazil, Europe, and other markets to support local businesses.

Giti Tire continues to strengthen its organization and invest in new technology to meet the rising demands of OEM partners. Along with new product development and replacement sales, this will enable Giti Tire to continue to grow market share in coming years.



Giti Tire won General Motors Quality Excellence awards from 2012 to 2014, in addition to many other awards in recent years from various OEM companies.



Table Of Contents



Sport Active



MAXTOUR All Season



CHAMPIRO FE1

PCR



MAXTOUR



CHAMPIRO 728



CHAMPIRO VP1

SUV



SAVERO HT PLUS



SAVERO HT2



ADVENTURO AT³

VAN



MAXMILER EX



MAXMILER Pro



SUPER TRAVELLER 668



CHAMPIRO UHP^{AS}



CHAMPIRO UHP1



CHAMPIRO 228



CHAMPIRO I28



CHAMPIRO 75



CHAMPIRO 528



ADVENTURO A/T II



ADVENTURO A/T



ADVENTURO M/T



Sport Active

The new SportActive is specifically developed for high powered rear and front wheel drive premium cars, with superb traction, immediate steering response and ultimate driving control in dry and wet conditions.



Features

NEW top tread compound.

Innovative new profile

Special design wide grooves and sipes

New block stiffness

Benefits

- ▶ Endures long durability and constant performances throughout the tire life.
- ▶ Firm high speed HANDLING and ULTIMATE GRIP
- ▶ Short braking distances on wet and dry roads, REDUCED AQUAPLANING
- ▶ Optimal CORNERING and handling

Sport Active



Inch	Series	Size	Load Index	Speed Rating	UTQG	 Tread Depth mm	 Overall Diameter mm	Side Wall
19	35	225/35R19	88	Y		7.7	641	BSW
	35	235/35R19	91	Y		7.7	647	BSW
	35	245/35R19	93	Y		7.7	655	BSW
	35	255/35R19	96	Y		7.7	661	BSW
	40	225/40R19	93	Y		7.7	663	BSW
	40	255/40R19	100	Y		7.7	687	BSW
	45	225/45R19	96	W		7.7	685	BSW
	35	255/35R18	94	Y		7.7	635	BSW
18	35	265/35R18	97	Y		7.7	643	BSW
	40	225/40R18	92	Y		7.7	637	BSW
	40	235/40R18	95	W		7.7	645	BSW
	40	235/40R18	95	Y		7.7	645	BSW
	40	245/40R18	97	Y		7.7	653	BSW
	45	225/45R18	95	W		7.7	659	BSW
	45	235/45R18	98	W		7.7	669	BSW
	45	245/45R18	100	W		7.7	677	BSW
	45	255/45R18	103	W		7.7	687	BSW
	55	255/55R18	109	W		7.7	737	BSW
	40	205/40R17	84	W		7.7	596	BSW
	40	215/40R17	87	W		7.7	604	BSW
17	40	245/40R17	91	Y		7.7	628	BSW
	40	255/40R17	98	Y		7.7	636	BSW
	45	205/45R17	88	W		7.7	616	BSW
	45	215/45R17	91	W		7.7	626	BSW
	45	225/45R17	94	W		7.7	634	BSW
	45	225/45R17	91	W		7.7	634	BSW
	45	235/45R17	97	W		7.7	644	BSW
	45	245/45R17	99	W		7.7	652	BSW
	50	225/50R17	98	W		7.7	658	BSW
	45	195/45R16	84	V		7.7	582	BSW
16	45	205/45R16	87	W		7.7	590	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall



MAXTOUR All Season



Features

NEW long durable tread compound

Variable pitch tread blocks

Lateral grooves and increase number of sipes

Wide circumferential grooves

Benefits

► Deliver long mileage

► Incredibly quiet and smooth running tire

► Excellent traction and efficiently pump out water and slush for confident all season and summer driving

► Effective water drainage to reduce hydroplaning

MAXTOUR All Season



Inch	Series	Size	Load Index	Speed Rating	UTQG	 Tread Depth mm	 Overall Diameter mm	Side Wall
16	55	205/55R16	91	H	520AA	7.9	632	BSW
	55	215/55R16	97	H	520AA	8	642	BSW
	60	205/60R16	92	T	580AB	7.9	652	BSW
	60	205/60R16	92	H	520AA	7.9	652	BSW
	60	225/60R16	98	H	520AA	8.1	676	BSW
	60	225/60R16	98	T	580AB	8.1	676	BSW
	60	235/60R16	100	T	580AB	8.1	688	BSW
	65	205/65R16	95	H	520AA	7.9	672	BSW
	65	215/65R16	98	T	580AB	8	686	BSW
	65	225/65R16	100	H	520AA	8.1	698	BSW
	65	235/65R16	103	T	580AB	8.1	712	BSW
	60	185/60R15	84	T	580AB	7.8	603	BSW
15	60	195/60R15	88	H	520AA	7.8	615	BSW
	60	195/60R15	88	T	580AB	7.8	615	BSW
	60	205/60R15	91	H	520AA	7.9	627	BSW
	60	215/60R15	94	T	580AB	8	639	BSW
	65	175/65R15	84	H	520AA	7.8	609	BSW
	65	185/65R15	88	H	520AA	7.8	621	BSW
	65	185/65R15	88	T	580AB	7.8	621	BSW
	65	205/65R15	94	H	520AA	7.9	647	BSW
	65	205/65R15	94	T	580AB	7.9	647	BSW
	65	215/65R15	96	T	580AB	8	661	BSW
	70	205/70R15	96	T	580AB	7.9	669	BSW
	70	215/70R15	98	T	580AB	8	683	BSW
14	70	225/70R15	100	T	580AB	8.1	697	BSW
	75	205/75R15	97	T	580AB	7.9	689	BSW
	75	215/75R15	100	T	580AB	8	703	BSW
	75	225/75R15	102	T	580AB	8.1	719	BSW
	60	185/60R14	82	H	520AA	7.8	578	BSW
	60	195/60R14	86	H	520AA	7.8	590	BSW
	65	175/65R14	82	T	580AB	7.8	584	BSW
	65	185/65R14	86	T	580AB	7.8	596	BSW
	70	175/70R14	84	T	580AB	7.8	602	BSW
	70	185/70R14	88	H	520AA	7.8	616	BSW
	70	195/70R14	91	T	580AB	7.8	630	BSW
	70	205/70R14	98	T	580AB	7.9	644	BSW
	75	185/75R14	89	T	580AB	7.8	634	BSW
	75	195/75R14	92	T	580AB	7.8	648	BSW
	75	205/75R14	95	T	580AB	7.9	664	BSW
13	70	175/70R13	82	T	580AB	7.8	576	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall



ALL ROUND PREMIUM COMFORT

CHAMPIRO FE1

The CHAMPIRO FE1 is GT Radial latest high performance tyre, combining superb mileage, quiet and smooth drive, great handling and an eye on fuel savings.”



Features

- Wide long grooves
- Edge of sipes and blocks
- Special tread compound
- Completely new profile design
- Variant pitch arrangement of tread

Benefits

- Excellent performances in WET CONDITIONS
- Effective water drainage for superb WET PERFORMANCE
- REDUCED HEAT GENERATION, improved rolling resistance
- QUIET AND COMFORTABLE ride
- Reduced NOISE emission

CHAMPIRO FE1

ALL ROUND PREMIUM COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
17	50	205/50ZR17	93	W	420AA	7.7	638	BSW
	50	215/50ZR17	95	W	420AA	7.7	648	BSW
	50	225/50ZR17	98	W	420AA	7.7	658	BSW
	55	215/55ZR17	94	W	420AA	7.7	668	BSW
	55	225/55ZR17	101	W	420AA	7.7	680	BSW
16	50	195/50R16	88	V	420AA	7.7	602	BSW
	55	195/55R16	91	V	420AA	7.7	620	BSW
	55	205/55R16	91	V	420AA	7.7	632	BSW
	55	205/55R16	94	V	420AA	7.7	632	BSW
	55	205/55ZR16	94	W	420AA	7.7	632	BSW
	55	215/55ZR16	97	W	420AA	7.7	642	BSW
	55	225/55ZR16	99	W	420AA	7.7	654	BSW
	60	205/60R16	96	V	420AA	7.7	652	BSW
	60	205/60R16	96	H	420AA	7.7	652	BSW
	60	215/60R16	99	V	420AA	7.7	664	BSW
15	50	195/50R15	82	V	420AA	7.7	577	BSW
	55	185/55R15	82	V	420AA	7.7	585	BSW
	55	195/55R15	85	V	420AA	7.7	595	BSW
	60	185/60R15	84	H	420AA	7.7	603	BSW
	60	195/60R15	88	V	420AA	7.7	615	BSW
	60	195/60R15	88	H	420AA	7.7	615	BSW
	60	205/60R15	91	V	420AA	7.7	627	BSW
	65	175/65R15	84	H	420AA	7.7	609	BSW
	65	185/65R15	88	H		7.7	621	BSW
	65	195/65R15	91	H	420AA	7.7	635	BSW
	65	195/65R15	91	V	420AA	7.7	635	BSW
	65	205/65R15	94	V	420AA	7.7	647	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall

ULTRA HIGH PERFORMANCE



CHAMPIRO UHP^{AS}

For vehicle owners requiring Ultra-High Performance or grand touring tires, the CHAMPIRO UHP AS delivers excellent straight-line stability, cornering grip, and braking capabilities in both dry and wet conditions, providing excellent grip and long tread life.



Features

New, Advanced Tread Compound

Full Depth Sipes

Four Wide Circumferential Grooves

Center Rib Design

Rim Protector

Benefits

- ▶ Delivers long tread life and grip performance in different seasons and conditions

- ▶ Provide improved performance throughout the life of the tire

- ▶ Reduces hydroplaning for improved wet performance

- ▶ Delivers straight line stability and crisp steering response

- ▶ Protects wheels from curb damage

CHAMPIRO UHP^{AS}

ULTRA HIGH PERFORMANCE



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
17	45	225/45ZR17	94	W	500AA	8.2	634	BSW
	45	235/45ZR17	97	W	500AA	8.2	644	BSW
	45	245/45ZR17	95	W	500AA	8.2	652	BSW
	45	255/45ZR17	98	W	500AA	8.2	662	BSW
	50	205/50ZR17	93	W	500AA	8.2	638	BSW
	50	215/50ZR17	91	W	500AA	8.2	648	BSW
	50	225/50ZR17	94	W	500AA	8.2	658	BSW
	55	215/55R17	94	V	500AA	8.2	668	BSW
	55	225/55ZR17	97	W	500AA	8.2	680	BSW
	55	235/55ZR17	99	W	500AA	8.2	690	BSW
16	45	205/45ZR16	87	W	500AA	8.2	590	BSW
	50	195/50R16	84	V	500AA	8.2	602	BSW
	50	205/50ZR16	87	V	500AA	8.2	612	BSW
	50	225/50ZR16	92	W	500AA	8.2	632	BSW
	50	245/50ZR16	97	W	500AA	8.2	652	BSW
	55	205/55R16	91	V	500AA	8.2	632	BSW
	55	225/55ZR16	95	W	500AA	8.2	654	BSW
	60	225/60R16	98	V	500AA	8.2	676	BSW
15	55	195/55R15	85	V	500AA	8.2	595	BSW
	55	205/55R15	88	V	500AA	8.2	607	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall

ULTRA HIGH PERFORMANCE



CHAMPIRO UHP1

A proven Ultra-High Performance tire designed to perform to high levels of stability, control, turn-in, and grip in the curves in both wet and dry.



Features

Strong integrated shoulder blocks

High Silica content tread formula

Four deep, wide circumferential grooves

Center rib design

Optimized pitch variance tread design

Benefits

- Improved cornering force and traction
- Improves wet and dry handling
- Ensures efficient water dispersion and wet performance
- Ensures linear stability and crisp steering response
- Reduces tire noise level for quieter ride

CHAMPIRO UHP1

ULTRA HIGH PERFORMANCE



Inch	Series	Size	Load Index	Speed Rating	UTQG	 Tread Depth mm	 Overall Diameter mm	Side Wall
17	50	205/50ZR17	93	W	280AAA	7	638	BSW
	50	215/50ZR17	95	W	280AAA	7	648	BSW
	50	225/50ZR17	98	W	280AAA	7	658	BSW
	55	215/55ZR17	94	W	280AAA	7	668	BSW
	55	225/55ZR17	101	W	280AAA	7	680	BSW
16	40	215/40ZR16	86	W	280AAA	7	578	BSW
	45	195/45R16	84	V	280AAA	7	582	BSW
	45	205/45ZR16	87	W	280AAA	7	590	BSW
	50	195/50R16	88	V	280AAA	7	602	BSW
	50	205/50ZR16	91	W	280AAA	7	612	BSW
	50	225/50ZR16	96	W	280AAA	7	632	BSW
	55	195/55R16	91	V	280AAA	7	620	BSW
	55	205/55R16	91	V	280AAA	7	632	BSW
	55	205/55ZR16	94	W	280AAA	7	632	BSW
	55	215/55ZR16	97	W	280AAA	7	642	BSW
	55	225/55ZR16	99	W	280AAA	7	654	BSW
15	45	195/45R15	78	V	280AAA	7	557	BSW
	50	195/50R15	82	V	280AAA	7	577	BSW
	50	205/50R15	89	V	280AAA	7	587	BSW
	55	195/55R15	85	V	280AAA	7	595	BSW
	55	205/55R15	88	V	280AAA	7	607	BSW

UTQG Uniform Tire Quality Grade **BSW** Black Side Wall



PREMIUM COMFORT

CHAMPIRO 228

CHAMPIRO 228 combines wet handling capabilities and premium driving comfort with high safety standards.



Features

- New Compound with NANOTEK Silica Technology
- “Frequency Disturber” tread design
- Z Sipes on shoulder blocks
- 4 Wide longitudinal grooves

Benefits

- ▶ Provides excellent grip on wet and dry roads
- ▶ Cancels out noise signals to provide a quieter ride
- ▶ Decreases noise without compromising vehicle cornering performance
- ▶ Ensures quick water evacuation to prevent aquaplaning

CHAMPIRO 228

PREMIUM COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
18	60	225/60R18	100	V	320AA	8.4	727	BSW
17	50	225/50R17	94	V	320AA	8.1	658	BSW
	50	235/50R17	96	V	320AA	8.2	668	BSW
17	55	215/55R17	94	V	320AA	8.1	668	BSW
	55	235/55R17	99	H	380AA	8.2	690	BSW
16	65	215/65R17	99	H	380AA	8.1	712	BSW
	50	205/50R16	87	V	320AA	8	612	BSW
	55	195/55R16	87	V	320AA	7.6	620	BSW
	55	195/55R16	91	H	380AA	7.6	620	BSW
	55	205/55R16	91	V	320AA	8	632	BSW
	55	205/55R16	91	H	380AA	8	632	BSW
	55	215/55R16	93	V	320AA	8.1	642	BSW
	55	225/55R16	95	V	320AA	8.1	654	BSW
	60	195/60R16	89	H	380AA	7.9	640	BSW
	60	205/60R16	92	V	320AA	8	652	BSW
15	60	215/60R16	95	V	320AA	8.1	664	BSW
	60	225/60R16	98	V	320AA	8.1	676	BSW
	50	195/50R15	82	V	320AA	7.9	577	BSW
	50	195/50R15	82	H	380AA	7.9	577	BSW
	55	185/55R15	82	V	320AA	7.8	585	BSW
	55	195/55R15	85	V	320AA	7.9	595	BSW
	60	185/60R15	84	H	380AA	7.7	603	BSW
	60	195/60R15	88	V	320AA	7.9	615	BSW
	60	205/60R15	91	V	320AA	8	627	BSW
	60	215/60R15	94	H	380AA	8.1	639	BSW
14	65	185/65R15	88	H	380AA	7.8	621	BSW
	65	195/65R15	91	H	380AA	7.9	635	BSW
	65	195/65R15	91	V	320AA	7.9	635	BSW
	65	205/65R15	94	V	320AA	8	647	BSW
	55	185/55R14	80	H	380AA	7.8	560	BSW
14	60	185/60R14	82	H	380AA	7.8	578	BSW
	60	195/60R14	86	H	380AA	7.9	590	BSW
	65	185/65R14	86	H	380AA	7.8	596	BSW


UTQG Uniform Tire Quality Grade BSW Black Side Wall



COMFORT

CHAMPIRO 128

The CHAMPIRO 128 tire is an ideal choice for drivers desiring high-performance control attributes and outstanding mileage.



Features

- Special compound and deeper tread depth
- Optimized casing profile and variable pitch
- Circumferential central rib with interlocking blocks and lugs
- Dynamic pattern with 4 wide straight grooves
- Extended shoulder grooves

Benefits

- ▶ Provides high mileage in daily driving
- ▶ Quite and comfort driving
- ▶ Enhances handling, traction and braking
- ▶ Effective water drainage for superb wet performance
- ▶ Provides enhanced cornering

CHAMPIRO I28

COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
17	55	225/55R17	97	V	260AA	8.1	680	BSW
16	55	205/55R16	91	V	260AA	8	632	BSW
	55	215/55R16	93	V	260AA	8.1	642	BSW
	60	205/60R16	92	H	460AA	8.2	652	BSW
	60	215/60R16	95	H	460AA	8.3	664	BSW
	60	225/60R16	98	H	460AA	8.4	676	BSW
	60	235/60R16	100	H	460AA	8.5	688	BSW
15	55	195/55R15	85	V	260AA	7.9	595	BSW
	60	185/60R15	88	H	460AA	8.1	603	BSW
	60	195/60R15	88	H	460AA	8.1	615	BSW
	60	205/60R15	91	H	460AA	8.2	627	BSW
	65	185/65R15	88	H	460AA	8.1	621	BSW
	65	205/65R15	94	H	460AA	8.2	647	BSW
	65	215/65R15	96	H	460AA	8.3	661	BSW
	60	165/60R14	75	H	460AA	7.9	554	BSW
14	60	175/60R14	79	H	460AA	8	566	BSW
	60	185/60R14	82	H	460AA	8.1	578	BSW
	60	195/60R14	86	H	460AA	8.1	590	BSW
	65	165/65R14	79	T	460AA	7.9	570	BSW
	65	175/65R14	82	H	460AA	8	584	BSW
	65	185/65R14	86	H	460AA	8.1	596	BSW
	65	195/65R14	89	H	460AA	8.1	610	BSW
13	65	165/65R13	77	T	460AA	7.9	544	BSW

UTQG Uniform Tire Quality Grade **BSW** Black Side Wall

MILEAGE



MAXTOUR

MAXTOUR offers high mileage, due to its durable and long-lasting components. The tire is designed to achieve maximum tread life without compromising performance.



Features

Advanced tread pattern

Special structure design

Enhanced tread compound and
low sea-land-ratio

Benefits

► Smooth, quiet and comfort

► Reliable endurance and durability

► Extended tread life

MAXTOUR

MILEAGE



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
15	70	215/70R15	98	T	620AB	8.9	683	BSW
	70	215/70R15	98	T	620AB	8.9	683	WR
	70	225/70R15	100	T	620AB	9	697	BSW
	70	235/70R15	103	T	620AB	9.1	711	BSW
	70	235/70R15	103	T	620AB	9.1	711	WR
	75	205/75R15	97	T	620AB	9.4	689	BSW
	75	215/75R15	100	T	620AB	9.5	703	BSW
	75	225/75R15	102	T	620AB	9.6	719	BSW
	75	235/75R15	105	T	620AB	9.7	733	BSW
14	60	185/60R14	82	T	620AB	9	578	BSW
	60	195/60R14	86	T	620AB	9.1	590	BSW
	65	175/65R14	82	T	620AB	8.9	584	BSW
	65	185/65R14	86	T	620AB	9	596	BSW
	70	185/70R14	88	T	620AB	9.2	616	BSW
	70	195/70R14	91	T	620AB	8.7	630	BSW
	70	205/70R14	95	T	620AB	8.8	644	BSW
	75	185/75R14	89	T	620AB	9.2	634	BSW
	75	195/75R14	92	T	620AB	9.3	648	BSW
	75	205/75R14	95	T	620AB	9.4	664	BSW
	80	175/80R14	88	T	620AB	8.8	636	BSW
	80	185/80R14	91	T	620AB	8.9	652	BSW
13	70	175/70R13	82	T	620AB	9.1	576	BSW
	70	185/70R13	86	T	620AB	9.2	590	BSW
12	70	145/70R12	69	T	620AB	8.8	509	BSW
	70	155/70R12	73	T	620AB	8.9	523	BSW
	70	155/70R12	73	T	620AB	8.9	523	RWL
	70	165/70R12	77	T	620AB	9	537	BSW
	70	165/70R12	77	T	620AB	9	537	RWL
	70	175/70R12	80	S	620AB	9.1	551	BSW
	80	145/80R12	74	T	620AB	8.5	537	BSW

UTQG Uniform Tire Quality Grade

BSW Black Side Wall

WR White Ring

RWL Raised White Letter



COMFORT

CHAMPIRO 728

CHAMPIRO 728 is built to provide comfort and deliver high-mileage driving.



Features

Circumferential center ribs

Variable pitch pattern

Special Compound

Benefits

- ▶ Delivers excellent handling and maneuverability
- ▶ Quiet and comfortable ride
- ▶ Provides high mileage

CHAMPIRO 728

COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
15	70	195/70R15	97	T	460AA	7.8	655	BSW
	70	205/70R15	96	H	460AA	7.9	669	BSW
	70	215/70R15	98	H	460AA	8	683	BSW
14	70	165/70R14	81	T	460AA	7.6	588	BSW
	70	175/70R14	84	H	460AA	7.7	602	BSW
	70	185/70R14	88	H	460AA	7.8	616	BSW
	70	195/70R14	96	T	460AA	7.8	630	BSW
	70	205/70R14	98	H	460AA	7.9	644	BSW
13	70	145/70R13	71	T	460AA	7.4	534	BSW
	70	155/70R13	75	T	460AA	7.6	548	BSW
	70	165/70R13	79	T	460AA	7.6	562	BSW
	70	175/70R13	82	H	460AA	7.7	576	BSW
	70	185/70R13	86	H	460AA	7.3	590	BSW

UTQG Uniform Tire Quality Grade **BSW** Black Side Wall

ALL-AROUND COMFORT



CHAMPIRO VP1

As a versatile tire, CHAMPIRO VP1 balances control, comfort, security and high mileage in all weather conditions. It is designed especially for drivers of family sedans, wagons and crossovers.



Features

Four deep, wide circumferential tread grooves

Stable shoulder block with lateral grooves

Continuous circumferential center rib

Optimized tread block design with integral lateral grooves and sipes

Advanced tread compound

Benefits

► Provide excellent water channeling and anti-hydroplaning performance

► Reduces tread block movement and ensures quick steering response and cornering grip

► Improves straight line stability

► Provides wet handling capabilities and reduces road noise

► Generates excellent grip in wet and dry conditions, and delivers reduced rolling resistance for better fuel efficiency

CHAMPIRO VP1

ALL-AROUND COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
18	60	P225/60R18	99	H	420AB	8.1	727	BSW
	60	P235/60R18	102	H	420AB	8.1	739	BSW
	65	P235/65R18	104	T	420AB	8.1	763	BSW
17	50	215/50R17	95	V	420AB	8	648	BSW
	50	225/50R17	94	V	420AB	8.1	658	BSW
	55	215/55R17	94	V	420AB	8	668	BSW
	55	225/55R17	97	V	420AB	8.1	680	BSW
	55	235/55R17	99	H	420AB	8.1	690	BSW
	60	P215/60R17	95	T	420AB	8	690	BSW
	60	P225/60R17	98	T	420AB	8.1	702	BSW
	60	235/60R17	102	T	420AB	8.1	714	BSW
	65	P215/65R17	98	T	420AB	8	712	BSW
	65	225/65R17	102	H	420AB	8.1	724	BSW
	65	P235/65R17	103	T	420AB	8.1	738	BSW
16	55	195/55R16	91	H	420AB	7.9	620	BSW
	55	205/55R16	91	V	420AB	8	632	BSW
	60	205/60R16	92	H	420AB	7.9	652	BSW
	60	P205/60R16	91	V	420AB	7.9	652	BSW
	60	P215/60R16	94	T	420AB	8	664	BSW
	60	P215/60R16	94	H	420AB	8	664	BSW
	60	P215/60R16	94	V	420AB	8	664	BSW
	60	215/60R16	95	H	420AB	8	664	BSW
	60	225/60R16	98	H	420AB	8.1	676	BSW
	60	P225/60R16	97	T	420AB	8.1	676	BSW
	60	P235/60R16	99	T	420AB	8.1	688	BSW
	60	235/60R16	100	H	420AB	8.1	688	BSW
	65	215/65R16	98	T	420AB	8	686	BSW
	65	225/65R16	100	H	420AB	8.1	698	BSW
	65	235/65R16	103	T	420AB	8.1	712	BSW
15	50	195/50R15	82	V	420AB	7.9	577	BSW
	55	185/55R15	82	H	420AB	7.8	585	BSW
	55	195/55R15	85	H	420AB	7.9	595	BSW
	60	P185/60R15	84	T	420AB	7.7	603	BSW
	60	185/60R15	84	H	420AB	7.8	603	BSW
	60	195/60R15	88	H	420AB	7.8	615	BSW
	60	P195/60R15	87	T	420AB	7.8	615	BSW
	60	205/60R15	91	H	420AB	7.9	627	BSW
	60	205/60R15	91	V	420AB	7.9	627	BSW
	60	215/60R15	94	H	420AB	8	639	BSW
	65	175/65R15	84	H	420AB	7.6	609	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall

CHAMPIRO VP1

ALL-AROUND COMFORT



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
15	65	185/65R15	88	H	420AB	7.9	621	BSW
	65	195/65R15	95	T	420AB	7.8	635	BSW
	65	195/65R15	91	H	420AB	7.8	635	BSW
	65	205/65R15	94	H	420AB	7.9	647	BSW
	65	P205/65R15	92	T	420AB	7.9	647	BSW
	65	P215/65R15	95	T	420AB	8	661	BSW
	65	215/65R15	96	H	420AB	8	661	BSW
	70	P205/70R15	95	T	420AB	7.9	669	BSW
	70	P215/70R15	97	T	420AB	8	683	BSW
	70	P225/70R15	100	T	420AB	8.1	697	BSW
	70	P235/70R15	102	T	420AB	8.1	711	BSW
	75	P205/75R15	97	S	420AB	7.9	689	BSW
	75	P215/75R15	100	S	420AB	8	703	BSW
	75	P225/75R15	102	S	420AB	8.1	719	BSW
	75	P235/75R15	105	S	420AB	8.1	733	BSW
14	60	185/60R14	82	H	420AB	7.7	578	BSW
	60	195/60R14	86	H	420AB	7.8	590	BSW
	65	155/65R14	75	T	420AB	7.4	558	BSW
	65	165/65R14	79	T	420AB	7.5	570	BSW
	65	175/65R14	82	T	420AB	7.6	584	BSW
	65	185/65R14	86	H	420AB	7.7	596	BSW
	65	P185/65R14	85	T	420AB	7.7	596	BSW
	65	195/65R14	89	T	420AB	7.7	610	BSW
	70	165/70R14	81	T	420AB	7.5	588	BSW
	70	175/70R14	88	T	420AB	7.6	602	BSW
	70	185/70R14	88	H	420AB	7.7	616	BSW
	70	195/70R14	91	T	420AB	7.8	630	BSW
	70	205/70R14	98	T	420AB	7.9	644	BSW
	75	P185/75R14	89	S	420AB	7.7	634	BSW
	75	P195/75R14	92	S	420AB	7.8	648	BSW
	75	P205/75R14	95	S	420AB	7.9	664	BSW
13	60	175/60R13	77	H	420AB	7.7	540	BSW
	65	155/65R13	73	T	420AB	7.4	532	BSW
	65	165/65R13	77	T	420AB	7.5	544	BSW
	70	145/70R13	71	T	420AB	7.3	534	BSW
	70	155/70R13	75	T	420AB	7.4	548	BSW
	70	165/70R13	79	T	420AB	7.5	562	BSW
	70	175/70R13	82	T	420AB	7.6	576	BSW
	70	185/70R13	86	T	420AB	7.7	590	BSW
12	80	155/80R12	77	T	420AB	7.4	553	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall



COMFORT



CHAMPIRO 75

The white-sidewall 75 series CHAMPIRO 75 is a perfect choice for drivers who desire comfort and good mileage.

Features

Variable pitch pattern

Special compound and deeper tread depth

Wide tread and wide lateral grooves

Benefits

► Quiet and comfortable ride

► Provides high mileage

► Excellent handling and maneuverability

Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
15	75	P205/75R15	97	S	460AB	8.4	689	WR
	75	P215/75R15	100	S	460AB	9.1	703	WR
	75	P215/75R15	100	S	460AB	9.1	703	OWL
	75	P225/75R15	102	S	460AB	9.2	719	WR
	75	P235/75R15	105	S	460AB	9.3	733	WR
14	75	P185/75R14	89	S	460AB	8.2	634	WR
	75	P195/75R14	92	S	460AB	8.3	648	WR
	75	P205/75R14	95	S	460AB	8.4	664	WR

UTQG Uniform Tire Quality Grade OWL Outline White Letter WR White Ring



PREMIUM PERFORMANCE SUV

CHAMPIRO 528

CHAMPIRO 528 has a modern appearance that goes along with its top-level performance. This premium SUV tire delivers the control, handling and stability that performance SUV drivers demand.



Features

Unique and dynamic tread design with progressive elements

Streamlined high-angle grooves

Wide casing profile and variable pitch design

Rim Protector

Benefits

- ▶ Outstanding handling stability
- ▶ Efficient water dispersion at high speeds and wet traction
- ▶ Comfortable and quiet performance
- ▶ Protects wheels from curb damage

CHAMPIRO 528

PREMIUM PERFORMANCE SUV



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
22	35	265/35R22	102	V	300AA	8.3	745	BSW
	40	305/40R22	114	V	300AA	8.7	803	BSW
	45	285/45R22	114	V	300AA	8.5	815	BSW
	45	305/45R22	118	V	300AA	8.7	833	BSW
20	45	275/45R20	110	V	300AA	8.4	756	BSW
	50	285/50R20	116	V	300AA	8.5	794	BSW
	50	295/50R20	118	V	300AA	8.6	804	BSW
	55	275/55R20	117	V	300AA	8.6	810	BSW
19	50	255/50R19	103	V	300AA	8.4	739	BSW
18	55	255/55R18	109	V	300AA	8.4	737	BSW
	60	235/60R18	103	V	300AA	8.3	739	BSW
17	65	235/65R17	104	V	300AA	8.3	738	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall



Wide tread contact patch provides excellent grip, maneuverability and braking




Circumferential central rib for high speed stability and control



Streamlined pattern and dual circumferential grooves for ultra-efficient water evacuation and wet traction



Robust shoulder pattern design provides tread stability, efficient response and precise cornering






LIGHT TRUCK AND SUV

SAVERO HT PLUS

SAVERO HT PLUS is designed especially for pick-ups, light trucks, and SUVs to deliver a high degree of both comfort and control and long mileage.



Features

Four vertical circumferential groove

Interlaced streamline horizontal grooves, assist with complex striae edge grooves

Open shoulder grooves

"S" shape perfect structure design

Benefits

► High-speed performance and excellent water dispersion

► Improved traction also suitable for snow driving

► Better heat desperation and turning capability

► Improved handling and durability

SAVERO HT PLUS

LIGHT TRUCK AND SUV



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
18	65	P235/65R18	104	T	460AB	10.3	763	OWL
17	60	235/60R17	102	H	460AA	8.5	714	BSW
	65	P235/65R17	104	T	460AB	10.3	738	BSW
	65	P245/65R17	105	T	460AB	10.3	750	BSW
	65	265/65R17	112	T	460AB	10.3	776	OWL
	65	265/65R17	112	T	460AB	10.3	776	BSW
	70	225/70R17	108	T	460AB	10.3	748	OWL
16	65	255/65R16	109	H	460AA	10.3	738	BSW
	70	215/70R16	100	H	460AA	10.3	708	BSW
	70	225/70R16	103	T	460AB	10.3	722	OWL
	70	235/70R16	106	T	460AB	10.3	736	OWL
	70	245/70R16	111	T	460AB	10.3	750	OWL
	70	255/70R16	111	T	460AB	10.3	764	OWL
	70	265/70R16	112	T	460AB	10.3	778	OWL
	75	LT225/75R16	115/112	R		11.9	744	BSW
15	75	P235/75R15	105	T	460AB	10.3	733	OWL
	80	215/80R15	102	S	460AB	10.2	725	BSW
		31x10.50R15LT	109	R		12.7	781	OWL

UTQG Uniform Tire Quality Grade BSW Black Side Wall OWL Outline White Letter

HIGHWAY PERFORMANCE



SAVERO HT2

SAVERO HT2 is a premium all-season highway light truck and SUV tire. It features a superior tread design that provides strong handling in both wet and dry condition, delivering a comfortable ride and long mileage.



Features

- Superior tread pattern design
 - New tread compound
 - Optimized casing tension technology
 - Advanced noise cancelling technology in tread block design
- ▶ Excellent handling and ride comfort
 - ▶ Outstanding grip and stability
 - ▶ Excellent balance of dry and wet handling
 - ▶ Effectively reduces road noise

Benefits

SAVERO HT2

HIGHWAY PERFORMANCE



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
20	45	275/45R20	110	V	520AB	8.2	756	BSW
	50	P245/50R20	102	V	520AB	8.2	754	BSW
	50	285/50R20	116	V	520AB	8.2	794	BSW
	55	P255/55R20	107	H	520AB	8.2	788	BSW
	55	P275/55R20	111	H	520AB	8.2	810	BSW
	60	P275/60R20	114	S	520AB	8.2	838	OWL
19	55	P245/55R19	103	S	520AB	8.2	753	BSW
18	55	255/55R18	109	V	520AB	8.2	737	BSW
	60	235/60R18	107	V	520AB	8.2	739	BSW
	60	P245/60R18	104	H	520AB	8.2	751	BSW
	60	P265/60R18	109	T	520AB	8.2	775	OWL
	65	P235/65R18	104	T	520AB	8.2	763	OWL
	65	P255/65R18	109	T	520AB	8.2	789	BSW
	65	P265/65R18	112	S	520AB	8.2	801	OWL
	65	P275/65R18	114	T	520AB	8.2	815	BSW
	65	LT275/65R18	123/120	S		10.2	815	OWL
	70	P255/70R18	112	T	520AB	8.2	815	BSW
	70	P265/70R18	114	S	520AB	8.2	829	OWL
	70	LT275/70R18	125/122	S		10.2	843	OWL
17	60	P275/60R17	110	T	520AB	8.2	762	OWL
	65	225/65R17	102	H	520AB	8.2	724	BSW
	65	P235/65R17	103	T	520AB	8.2	738	BSW
	65	P245/65R17	105	T	520AB	8.2	750	BSW
	65	P255/65R17	108	S	520AB	8.2	764	BSW
	65	P265/65R17	110	T	520AB	8.2	776	OWL
	65	P275/65R17	113	T	520AB	8.2	790	OWL
	70	P235/70R17	108	S	520AB	8.2	762	OWL
	70	P245/70R17	108	T	520AB	8.2	776	OWL
	70	LT245/70R17	119/116	R		10.2	776	BSW
	70	P255/70R17	110	S	520AB	8.2	790	OWL
	70	P265/70R17	113	T	520AB	8.2	804	OWL
	70	LT265/70R17	121/118	S		10.2	804	OWL
	75	P235/75R17	108	S	520AB	8.2	784	OWL
	75	LT245/75R17	121/118	S		10.2	800	BSW
	80	LT235/80R17	120/117	R		10.2	808	BSW

UTQG Uniform Tire Quality Grade BSW Black Side Wall OWL Outline White Letter

SAVERO HT2

HIGHWAY PERFORMANCE



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
16	65	P255/65R16	106	S	520AB	8.2	738	BSW
	70	P215/70R16	99	T	520AB	8.2	708	BSW
	70	P225/70R16	101	T	520AB	8.2	722	OWL
	70	P235/70R16	104	T	520AB	8.2	736	OWL
	70	P245/70R16	106	T	520AB	8.2	750	OWL
	70	P255/70R16	109	T	520AB	8.2	764	OWL
	70	P265/70R16	111	T	520AB	8.2	778	OWL
	70	275/70R16	114	H	520AB	8.2	792	OWL
	75	P225/75R16	106	S	520AB	8.2	744	OWL
	75	LT225/75R16	115/112	R		10.2	744	BSW
	75	P235/75R16	106	T	520AB	8.2	758	BSW
	75	P245/75R16	109	T	520AB	8.2	774	OWL
	75	LT245/75R16	120/116	S		10.2	774	OWL
	75	P265/75R16	114	T	520AB	8.2	804	OWL
	75	LT285/75R16	126/123	R		10.2	834	OWL
15	85	LT215/85R16	115/112	R		10.2	772	BSW
	85	LT235/85R16	120/116	R		10.2	806	BSW
	65	185/65R15	92	T	280AB	7.8	621	BSW
	70	P215/70R15	97	S	520AB	8.2	683	BSW
	70	255/70R15C LT	112/110	S		10.2	739	OWL
	75	P235/75R15	105	T	520AB	8.2	733	OWL
	75	LT235/75R15	104/101	R		10.2	733	OWL
		30x9.50R15	104	R		10.2	750	OWL
		31x10.50R15LT	109	R		10.2	775	OWL

UTQG Uniform Tire Quality Grade BSW Black Side Wall OWL Outline White Letter

ALL-TERRAIN



ADVENTURO A/T II

An all-terrain tire for light truck and SUV drivers who want an exciting pattern appearance and require off-road capabilities. Its large, self-cleaning block design allows for greater grip, traction and control on a variety of off-road condition.

Features

Special tread compound with big pattern blocks

Open shoulder grooves and wide lugs

Full nylon cap ply

Benefits

► Ensure steady directional stability in all-surface traction and all-weather condition

► Superior all-surface traction for all weather conditions

► Improve safety in all-surface conditions

ADVENTURO A/T II

ALL-TERRAIN

Inch	Series	Size	Load Index	Speed Rating	Tread Depth mm	Overall Diameter mm	Side Wall
16	75	LT215/75R16	107/104	S	11.9	728	OWL
	75	LT225/75R16	115/112	S	13.1	744	OWL
	75	LT285/75R16	122/119	S	13.3	834	OWL
	85	LT235/85R16	120/116	S	13.1	806	BSW
15	75	LT235/75R15	104/101	S	12.1	739	OWL
	75	LT235/75R15	110/107	S	12.1	739	OWL

OWL Outline White Letter

ADVANCED ALL-TERRAIN



ADVENTURO AT-AW

The ADVENTURO AT3 is an all-terrain tire designed for light truck and SUV drivers seeking aggressive looks with civilized on-road manners. The tire provides excellent handling and wet grip, with a comfortable ride on-road and superb off-road capability.



Features

- Enhanced tread compound
- Interlocked tread blocks and S-shaped central rib
- 3D grooves with chamfered edges
- Five-pitch pattern technology
- Rim protector

Benefits

- ▶ Provides excellent wet and dry grip, longer tread life, and cut/chip resistance
- ▶ Delivers excellent handling stability and improved grip on soft or loose surfaces
- ▶ Consistent off-road performance with reduced stone-drilling
- ▶ Helps reduce road noise for a quieter and more comfortable ride
- ▶ Defends wheel against curb damage

ADVENTURO AT-AW

ADVANCED ALL-TERRAIN



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
20	55	275/55R20	113	T	500AB	10.6	810	BSW
	60	275/60R20	115	T	500AB	10.6	838	BSW
18	65	P275/65R18	114	T	500AB	10.6	815	OWL
	65	LT275/65R18	123/120	S		12.6	815	OWL
	70	LT265/70R18	124/121	S		12.6	829	OWL
	70	LT275/70R18	125/122	S		12.6	843	OWL
17	70	LT245/70R17	119/116	S		12.6	776	OWL
	70	LT265/70R17	121/118	S		12.6	804	OWL
	70	LT285/70R17	121/118	S		12.6	832	OWL
	75	LT245/75R17	121/118	S		12.6	800	OWL
	80	LT235/80R17	120/117	S		12.6	808	OWL
16	75	LT225/75R16	115/112	S		12.6	744	OWL
	75	LT245/75R16	120/116	S		12.6	774	OWL
	75	LT265/75R16	123/120	S		12.6	804	OWL
	85	LT235/85R16	120/116	S		12.6	806	BSW

UTQG Uniform Tire Quality Grade OWL Outline White Letter BSW Black Side Wall

ADVANCED ALL-TERRAIN



ADVENTURO AT³

The ADVENTURO AT3 is an all-terrain tire designed for light truck and SUV drivers seeking aggressive looks with civilized on-road manners. The tire provides excellent handling and wet grip, with a comfortable ride on-road and superb off-road capability.



Features

- Enhanced tread compound
- Interlocked tread blocks and S-shaped central rib
- 3D grooves with chamfered edges
- Five-pitch pattern technology
- Rim protector

Benefits

- ▶ Provides excellent wet and dry grip, longer tread life, and cut/chip resistance
- ▶ Delivers excellent handling stability and improved grip on soft or loose surfaces
- ▶ Consistent off-road performance with reduced stone-drilling
- ▶ Helps reduce road noise for a quieter and more comfortable ride
- ▶ Defends wheel against curb damage

ADVENTURO AT³

ADVANCED ALL-TERRAIN



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
20	60	LT265/60R20	121/118	S		12.6	826	OWL
18	65	LT275/65R18	123/120	S		12.6	815	OWL
	65	LT285/65R18	125/122	S		12.6	827	OWL
	70	LT265/70R18	124/121	S		12.6	829	OWL
	70	LT275/70R18	125/122	S		12.6	843	OWL
17	70	LT245/70R17	119/116	S		12.6	776	OWL
	70	LT245/70R17	108/104	S		12.6	776	OWL
	70	LT265/70R17	121/118	S		12.6	804	OWL
	70	LT275/70R17	114/110	R		12.6	818	OWL
	70	LT285/70R17	121/118	S		12.6	832	OWL
	75	LT245/75R17	121/118	S		12.6	800	OWL
	80	LT235/80R17	120/117	S		12.6	808	OWL
	75	LT225/75R16	115/112	S		12.6	744	OWL
16	75	LT245/75R16	120/116	S		12.6	774	OWL
	75	LT265/75R16	112/109	S		12.6	804	OWL
	75	LT265/75R16	123/120	S		12.6	804	OWL
	75	LT285/75R16	126/123	R		12.6	834	OWL
	85	LT215/85R16	115/112	S		12.6	772	OWL
	85	LT235/85R16	120/116	S		12.6	806	BSW
		205R16C LT	110/108	S		12.6	736	OWL
15		31×10.50R15LT	109	S		12.6	775	OWL


UTQG Uniform Tire Quality Grade OWL Outline White Letter BSW Black Side Wall



ALL-TERRAIN

ADVENTURO A/T

An all-terrain tire for light trucks and SUVs designed to provide a great balance of highway and off-highway use for drivers who experience both conditions. The robust tread block design with shoulder-to shoulder sipes provides excellent traction and cornering grip.



Features

Particular compound and structure design, super deep grooves

Unique block tread design with multiple sipes

Wide tread pattern with deep solid blocks and lugs

Open shoulder design with wide grooves

Benefits

► Extend tire's life

► Extra off road traction

► Delivers superior handling and extended tread life

► Improves anti-hydroplaning capability and provides enhanced wet grip performance

ADVENTURO A/T

ALL-TERRAIN



Inch	Series	Size	Load Index	Speed Rating	UTQG	Tread Depth mm	Overall Diameter mm	Side Wall
17	70	LT265/70R17	121/118	S	OWL		11.9	804
16	70	LT225/70R16	102/99	S	OWL		10.7	722
	70	P275/70R16	114	T	OWL	400AB	10.2	792
	75	LT265/75R16	112/109	S	OWL		13.2	804
	85	LT235/85R16	120/116	S	BSW		13.1	806
15	75	P235/75R15	105	S	OWL	400AB	9.2	733
	75	LT235/75R15	104/101	S	OWL		12.1	733
		31x10.50R15LT	109	S	OWL		12.6	775

UTQG Uniform Tire Quality Grade BSW Black Side Wall OWL Outline White Letter

OFF ROAD MAXIMUM TERRAIN

ADVENTURO M/T

ADVENTURO M/T is a maximum traction tire that is the most aggressive and rugged tire in GT Radial line designed with large, pronounced tread blocks. It provides superb traction on rough, muddy and snowy terrain.



Features

- Aggressive pattern design
- High void ratio and pyramid shaped tread elements
- Special casing profile and solid shoulder pattern
- Reinforced casing construction

Benefits

- ▶ Outstanding traction in all weather conditions
- ▶ Excellent resistance to aquaplaning and self-cleaning performance
- ▶ Enhanced traction and cornering
- ▶ Superior overall resistance to damage

ADVENTURO M/T

OFF ROAD MAXIMUM TERRAIN



Inch	Series	Size	Load Index	Speed Rating	Tread Depth mm	Overall Diameter mm	Side Wall
16	70	LT305/70R16	118/115	Q	14.6	840	OWL
	75	LT225/75R16	115/112	Q	12.6	750	OWL
	75	LT245/75R16	120/116	Q	14.6	780	OWL
	75	LT265/75R16	123/120	Q	14.6	810	OWL
	75	LT285/75R16	122/119	Q	14.6	840	OWL
	85	LT235/85R16	120/116	Q	14.6	812	OWL
15	75	LT235/75R15	104/101	S	14.6	739	OWL
		31x10.50R15LT	109	Q	14.6	781	OWL
		33x12.50R15LT	108	Q	14.6	832	OWL

OWL Outline White Letter




SAFETY

MAXMILER EX

**MAXIMUM MILEAGE
ECONOMY
EXTRA LOAD CAPACITY**

MAXMILER EX is designed for modern, high speed commercial and passenger vans, delivering comfort and high-load capability.



Features

Optimized weight construction

Benefits

► Reduces fuel consumption and provides a high

Reinforced belt construction

► Enables a high load safely, even under speed

New bead design

► Reduces heat build up in high load conditions and extends the life of the tire

Silica based compound

► Combines good wet and dry handling with maximum mileage performance. Reduced heat and fuel consumption

MAXMILER EX

SAFETY



Inch	Series	Size	Load Index	Speed Rating	Tread Depth mm	Overall Diameter mm	Side Wall
16	60	195/60R16C LT	99/97	H	9.5	640	BSW
	60	215/60R16C LT	103/101	T	9.9	664	BSW
	65	195/65R16C LT	104/102	T	9.5	660	BSW
	65	205/65R16C LT	107/105	T	9.5	672	BSW
	65	215/65R16C LT	106/104	T	9.5	686	BSW
	65	225/65R16C LT	112/110	T	10.1	698	BSW
	65	235/65R16C LT	115/113	R	10.3	712	BSW
	75	175/75R16C LT	101/99(104)	R(N)	9.1	668	BSW
	75	185/75R16C LT	104/102	R	9.1	684	BSW
	75	195/75R16C LT	107/105	R	9.5	698	BSW
	75	205/75R16C LT	110/108	R	10.2	714	BSW
	75	205/75R16C LT	113/111	R	10.2	714	BSW
	75	215/75R16C LT	116/114	R	9.9	728	BSW
	75	225/75R16C LT	118/116	R	10.1	744	BSW
15	65	205/65R15C LT	102/100	T	9.7	647	BSW
	70	195/70R15C LT	104/102	R	9.5	655	BSW
	70	205/70R15C LT	106/104	R	9.7	669	BSW
	70	215/70R15C LT	109/107	S	9.9	683	BSW
	70	225/70R15C LT	112/110	R	10.1	697	BSW
14	65	175/65R14C LT	90/88	T	9.1	584	BSW
	70	165/70R14C LT	89/87	R	8.9	588	BSW
	75	215/75R14C LT	112/110	R	9.9	678	BSW
		185R14C LT	102/100	R	9.3	650	BSW
		195R14C LT	106/104	R	9.5	666	BSW

BSW Black Side Wall



PREMIUM MILEAGE

MAXMILER Pro

“New generation commercial tire with improved wear and durability for heavy usage on all roads.”

Features

Reinforced new casing construction

Flat tyre tread contour

New tread compound

Modern pattern design

Benefits

- ▶ **IMPROVES DURABILITY AND** robustness even in the toughest driving conditions
- ▶ Ensures a larger contact area with the ground, producing a **HIGHER WEAR VOLUME** and mileage whilst also improving vehicle handling
- ▶ Provides **HIGH LEVEL OF WET PERFORMANCE**
- ▶ Provides a very **LOW NOISE LEVEL**, improving both driver comfort and reducing environmental impact

MAXMILER Pro

PREMIUM MILEAGE



Inch	Series		Load Index	Speed Rating	Tread Depth mm	Overall Diameter mm	Side Wall
16	60	195/60 R16C LT	99/97	H	9.2	640	BSW
	60	215/60 R16C LT	103/101	H	9.2	664	BSW
	65	195/65 R16C LT	104/102	T	9.7	660	BSW
	65	205/65 R16C LT	107/105	T	10.2	672	BSW
	65	215/65 R16C LT	109/107	T	10.2	686	BSW
	65	225/65 R16C LT	112/110	T	10.2	698	BSW
	65	235/65 R16C LT	121/119	R	10.7	712	BSW
	70	215/70 R16C LT	108/106	T	10.2	708	BSW
	75	185/75 R16C LT	104/102	T	9.7	684	BSW
	75	195/75 R16C LT	107/105	R	10.2	698	BSW
	75	205/75 R16C LT	113/111	R	10.2	714	BSW
	75	215/75 R16C LT	116/114	R	10.2	728	BSW
	75	225/75 R16C LT	118/116	R	10.7	744	BSW
15	70	195/70 R15C LT	104/102	R	10.2	655	BSW
	70	205/70 R15C LT	106/104	R	10.2	669	BSW
	70	215/70 R15C LT	109/107	S	10.2	683	BSW
	70	225/70 R15C LT	112/110	R	10.7	697	BSW
14	65	175/65 R14C LT	90/88	T	9.2	584	BSW
		185 R14C LT	102/100	R	9.9	650	BSW
		195 R14C LT	106/104	R	9.7	666	BSW
13		165 R13C LT	94/92	R	8.7	596	BSW
		175 R13C	97/95	R	8.3	610	BSW
12		155 R12C LT	88/86	R	8.2	550	BSW

BSW Black Side Wall

HEAVY DUTY



SUPER TRAVELLER 668

SUPER TRAVELLER 668 is built for light buses and commercial light trucks.

Features

- High scrub-resistance compound and deeper depth
- Robust casing and bead
- Solid shoulder design
- Four longitudinal grooves

Benefits


- Delivers long mileage
- For resistance to road hazard damage
- Improves stability, wear and protection
- Excellent water evacuation for strong wet performance

Inch	Series	Load Index	Speed Rating	Tread Depth mm	Overall Diameter mm	Side Wall
16	6.50R16 LT	108/107	N	9.7	750	BSW
	7.00R16 LT	115/110	N	10.7	775	BSW
	7.50R16 LT	122/118	N	11.2	805	BSW
15	7.00R15 LT	110/105	N	10.7	750	BSW

BSW Black Side Wall



Designations, Load Index and Speed Rating



Before fitting, it is essential to check the different markings to ensure that the tire meets the maximum load and speed possibilities and/or the regulations in force.

SAFETY WARNING

1. Never inflate beyond 40PSI (275kPa) to seat beads.
2. Tires should always be installed by qualified technicians following RMA installation procedures.
3. Never mount tires on rims which are damaged or not smooth and clean.
4. Never mount a tire with a torn bead.
5. Never inflate a tire that is lying on the floor or other flat surface.
6. Always use a tire mounting machine with hold-down device or safety cage, or bolt to vehicle axle.

MOUNT ONLY ON A RIM OF EXACT SAME DIAMETER OF THE TIRE.

Speed Rating Symbol

SI	MPH	KM/H
B	31	50
C	37	60
D	40	65
E	43	70
F	50	80
G	56	90
J	62	100
K	68	110
L	75	120
M	81	130
N	87	140
P	93	150
Q	100	160
R	106	170
S	113	180
T	118	190
U	124	200
H	130	210
V	149	240
W	168	270
Y	186	300
(Y)	Above 186	Above 300

Load Capacity Index

LI	LBS	KG	LI	LBS	KG
67	677	307	101	1819	825
68	694	315	102	1874	850
69	716	325	103	1929	875
70	739	335	104	1984	900
71	761	345	105	2039	925
72	783	355	106	2094	950
73	805	365	107	2150	975
74	827	375	108	2205	1000
75	852	387	109	2271	1030
76	882	400	110	2337	1060
77	908	412	111	2403	1090
78	937	425	112	2469	1120
79	964	437	113	2535	1150
80	992	450	114	2601	1180
81	1018	462	115	2679	1215
82	1047	475	116	2756	1250
83	1073	487	117	2833	1285
84	1102	500	118	2910	1320
85	1135	515	119	2998	1360
86	1168	530	120	3086	1400
87	1201	545	121	3197	1450
88	1235	560	122	3307	1500
89	1279	580	123	3417	1550
90	1323	600	124	3527	1600
91	1356	615	125	3658	1650
92	1389	630	126	3748	1700
93	1433	650	127	3858	1750
94	1477	670	128	3968	1800
95	1521	690	129	4079	1850
96	1565	710	130	4189	1900
97	1609	730	131	4299	1950
98	1653	750	132	4409	2000
99	1764	775	133	4542	2060
100	1819	800	134	4674	2120

Load Range Chart

Load Range	Ply Rating	Load Range	Ply Rating
A	2	G	14
B	4	H	16
C	6	J	18
D	8	L	20
E	10	M	22
F	12	N	24

SUV Tire Size

 **15 - 22 Rim**
 **35 - 85 Series**


Series	Dimension	CHAMPIRO 528	SAVERO HT PLUS	SAVERO HT2	ADVENTURO AT3	ADVENTURO A/T II	ADVENTURO A/T	ADVENTURO M/T
70	P275/70R16					114T		
70	LT305/70R16						118/115Q	
70	P215/70R15			97S				
70	255/70R15C LT			112/110S				
75	LT245/75R17				121/118S			
75	LT215/75R16					107/104S		
75	LT225/75R16	115/112R	115/112R	115/112S	115/112S		115/112Q	
75	P235/75R16			106T				
75	LT245/75R16			120/116R	108/104S 120/116S		120/116Q	
75	P245/75R16			109T				
75	LT265/75R16	119/116R	123/120R	112/109S 123/120S		112/109S	123/120Q	
75	P265/75R16			114T				
75	LT285/75R16				122/119S		122/119Q	
75	LT235/75R15			104/101R	104/101S	104/101S	104/101S	
75	P235/75R15	105T	105T	105S		105S		
80	215/80R15	102S						
85	LT215/85R16			115/112S				
85	LT235/85R16	120/116R	120/116R	120/116S	120/116S	120/116S	120/116Q	
	30x9.50R15			104R				
	30x9.50R15LT					104S		
	31x10.50R15LT	109R	109R	109S		109S	109Q	
	33x12.50R15LT					108Q		

LT VAN Tire Size


 **15 - 22 Rim**
 **35 - 85 Series**

Series	Dimension	MAXMILER EX	MAXMILER RX	SUPER TRAV-ELER 668
60	195/60R16C LT	99/97H		
60	215/60R16C LT	103/101T		
65	195/65R16C LT	104/102T		
65	205/65R16C LT	107/105T		
65	215/65R16C LT	106/104T		
65	225/65R16C LT	112/110T		
65	235/65R16C LT	115/113R		
65	205/65R15C LT	102/100T		
65	175/65R14C LT	90/88T		
70	195/70R15C LT	104/102R		
70	205/70R15C LT	106/104R		
70	215/70R15C LT	109/107S		
70	225/70R15C LT	112/110R		
70	165/70R14C LT	89/87R		
75	175/75R16C LT	101/99R		
75	185/75R16C LT	104/102R		
75	195/75R16C LT	107/105R		
75	205/75R16C LT	110/108R 113/111R		
75	215/75R16C LT	116/114R		
75	225/75R16C LT	118/116R		
75	215/75R14C LT	112/110R		
	6.50R16 LT		108/107N	
	7.00R16 LT		115/110N	
	7.50R16 LT		122/118N	
	185R15C LT		103/102Q	
	7.00R15 LT		110/105N	
	175R14C LT		99/98N	
	185R14C LT		102/100R	102/100N
	195R14C LT		106/104R	106/104N
	205R14C LT		109/107N	
	155R13 LT		90/88Q	
	165R13C LT		94/93N	
	175R13C LT		97/95N	
	145R12C LT		80/78Q	
	155R12C LT		83/81N	
	6.50R16LT		110/105Q	

General function of tires for all types of vehicles




1. Weight-bearing
Air pressure and tire construction are important factors to carry and sustain the weight of vehicles.



2. Absorb shocks
Air pressure and tire construction reduces initial road vibrations and shocks before being muted again by the suspension .




3. Delivering power from the engine
Tires serve to deliver power from the engine to move the vehicle and also provides traction and braking performance .



4. Translating steering wheel movement
Tires are very important in controlling the direction of the vehicle, which will determine the maneuvering capability and stability in driving.

Understand tire size



Tires have its 'language' to communicate in the form of a series of numbers and letters to indicating data specification, brand and type. It is universal and has been agreed by all tire manufacturers worldwide.

Here are the meanings of these codes:

1. Tire width (in mm)
2. A tire's aspect ratio is the dimensional relationship of the tire's section height to section width, expressed as a percentage.
3. Diameter of wheel (in inches)
4. Load Index
5. Speed Index

Understand Load Index and Speed Rating

The Speed index is an assigned letter ranging from J to Z that corresponds to the reference maximum speed at the associated load index. Refer to the load index and speed rating tables below.

These two elements put together are called the service description and are mutually dependent. The table below gives the load index and the speed symbol with their corresponding value.

UTQG (Uniform Tire Quality Grades) Rating

The UTQG (Uniform Tire Quality Grades) rating is a labeling requirement by the U.S Department of Transportation for all tire manufacturers. The label of UTQG represents a tire's Treadwear, Traction and **Temperature** resistance. Traction and temperature resistance ratings are specific performance levels, while treadwear ratings are assigned by manufacturers following tests conducted and are reliable when comparing tires of the same brand.



The UTQG rating comprises of 3 components.

Treadwear

The treadwear grade indicates the wear rate of a tire and is a comparative rating based on test conducted by tire manufacturers. The grades are not an indication of actual mileage, but can be used as a relative comparison. For example, a grading of 400 should last twice as long as a tire graded 200, given similar driving conditions in the same brand.

Traction

Traction rating is an indication of a tire's ability to stop on wet pavement. The braking distance is indicated by ratings of "AA" (highest braking ability), "A", "B" and "C". Traction rating only indicates straight line wet braking and does not indicate wet cornering abilities of the tire.

Temperature

Temperature resistance rating indicates the tire's ability to withstand heat. It is graded according to a properly inflated and not overloaded tire. It is graded from "C", being the lowest, to "B" and "A" ratings.

Load Index (Symbol and maximum load in Lbs & Kg)

LI	Lbs	Kgs	LI	Lbs	Kgs	LI	Lbs	Kg	LI	Lbs	Kg
71	761	345	81	1019	462	91	1356	615	101	1819	825
72	783	355	82	1047	475	92	1389	630	102	1874	850
73	805	365	83	1074	487	93	1433	650	103	1929	875
74	827	375	84	1102	500	94	1477	670	104	1984	900
75	853	387	85	1135	515	95	1521	690	105	2039	925
76	882	400	86	1168	530	96	1565	710	106	2094	950
77	908	412	87	1201	545	97	1609	730	107	2149	975
78	937	425	88	1235	560	98	1653	750	108	2205	1000
79	963	437	89	1279	580	99	1709	775	109	2271	1030
80	992	450	90	1323	600	100	1764	800	110	2337	1060

Speed Rating (symbol and maximum speed in MpH & KmH)

	J	K	L	M	N	P	Q	R	S	T	H	V	W	Y
MpH	62	68	75	81	87	93	100	106	113	118	130	150	168	188
KmH	100	110	120	130	140	150	160	170	180	190	210	240	270	300

Note: A "ZR" may appear for tires having a maximum speed capability above 240km/h (150 mph)

Guide on when to replace your tyres



Every tire has a Tread Wear Indicator (TWI), which form a triangle \triangle located on the sidewall. TWI is an indicator of tire wear and is also a benchmark to you to check if your tire is worn out. Tires should be changed immediately when the tire tread has surpassed the indicators.



Worn out tires compromises handling and braking distance tremendously.



Do keep a lookout for physical signs stated below, even if the tires have not worn out yet




Bulges on tires

We recommend you to replace the tires immediately, due to high potential of tires bursting



Patches

A sign of potential air leak



Cracks

Normally on the tire's sidewall

Consult your nearest tire dealer if there are any signs of physical damage or deformity of your tires.

Tire tread patterns

There are many brands and patterns of tires available today. So how do you know that you are choosing the tires suitable for your driving needs? Generally, tire patterns can be differentiated into 3 categories. The Directional pattern, also known as Unidirectional, the Non-Directional pattern, also known as symmetric, and the Asymmetric pattern.

All three categories of tire patterns have different characteristics to provide for different needs of drivers.



Directional/ Unidirectional

Directional pattern tires have lateral grooves on both side of the tire which points in the same direction. It is usually in a "V-shaped" pattern.

Features:

- Increase water dispersion to provide good handling in both wet and dry road conditions
- Better steering and braking capabilities
- Usually available in bigger sizes (15" and above) and high speed index

Suitable for:

Drivers who want to have high speed performance level of the tire.



Non-directional/ Symmetric

Non-directional pattern tires have tread pattern that usually has continuous rib design or blocks which has the same features on both inside and outside tread face of the tire. It is normally in a "wave-like" pattern,

Features:

- Comfort, low noise design oriented tires
- Lateral grooves to provide water dispersion

Suitable for:

Drivers who want to have a comfortable and quiet drive.



Asymmetric

Asymmetric pattern tires have unique patterns differing on both sides of the tire tread. The outer tread area of the tire usually has larger grooves to disperse water to increase wet handling, while the inside tread area usually has smaller grooves to increase contact area with the road.

Features:

- Good handling capabilities on wet and dry roads
- Good high speed cornering capabilities

Suitable for:

Drivers who want tires with high performance capabilities.

Few tips to maximize your tire performance and durability

- Check your tires air pressure at least once a month. Adjust the air pressure according to the manufacturer's instruction manual
- Tire balancing and wheel alignment will increase tire mileage and maintains the performance of the tires
- Use only tire cleaners and water to clean your tires

Air pressure




The tire's air pressure standard for each vehicle is set by the **vehicle manufacturer** and can be found in various areas of your vehicle, such as at the end of the driver's door, at the bottom of the door or in part in the storage box at the door of the vehicle.

Low air pressure can cause damage to the side-wall, thus decreasing the load carrying capacity, and also consume more fuel. Hence the tire pressure should be checked regularly, at least once every month.




Note:

Allow the tires to cool down after driving before checking the air pressure in order to obtain a more accurate reading.




! Improper air pressure leads to irregular wear of the tires.


Wear and tear in the middle of the tire is caused by excessive air pressure. On the other hand, low air pressure results in uneven wear on both sides of the tire shoulder.



Correct air pressure
results in regular wear and tear of the tire, thus providing a longer tire life



Low air pressure
results in wear and tear on both sides of the tire shoulder, creating uneven wear of the tire




Excessive air pressure
results in wear and tear on the middle of the tire, which results in uneven wear of the tire

Rotate your tyre regularly to improve tire life

Regular tire rotation helps to prolong the tire's life and maintains optimum performance and mileage of the tires. Tires not rotated on regular basis will result in uneven wear and will also compromise the performance of the tires over time.

Rotation is required when the tire mileage reaches between 8000-10,000 km.

There are 2 different ways of tire rotation, the 4-Tire rotation and 5-Tire rotation.



4-Tire rotation


Can be done by diagonal, horizontal or vertical rotation

For diagonal rotation;

it is done by swapping the front left tire to right rear and front right tire with the rear left.


For horizontal rotation,

it is done by exchanging the front right wheel with the left front wheel. Likewise for the rear wheels, rear right tire will be exchanged with the left rear tire. This method is normally used for non-directional tires.



For vertical rotation,

it is done by swapping the front right tire with the back right tire, and the front left tire with the back left tire. This method is normally used for directional tread pattern tires.



5-Tires rotation (with spare tire)

5 tire rotation relatively similar to the 4 tire diagonal, except that the spare tire will also be rotated. The spare tire is to be mounted on the left rear, left rear tire moved to the front left. The left front tire will be moved to right back and right back to be moved to the front right.

Lastly, the right front tire will be used as the spare tire. This method of rotation is normally used for 4-wheel and all-wheel drive vehicles.

Note: Do not use the 5-Tire rotation method if the spare tire is of a different brand/model to the rest of the tires.
